

Massey Ferguson MF260 - 60 HP Turbo A Multipurpose Tractor



- High Performance, Fuel Efficient, Diesel Turbo Engine.
- Less Smoke Emission Due to Better Fuel Burning.
- Oil Cooler Added for Effective Cooling.
- High PTO Power for Efficient Operation of Tube Wells, Rotavators, Threshers etc.
- Robust Straddle Rear Axle.
- Efficient Oil Immersed Multi-Disc Brakes.
- Spring Suspension Deluxe Seat.

Buy Massey Ferguson MF 260 60HP Model 2019

Performance

Maximum Engine Power at 2,250 rpm	60 (B.S) hp*
Maximum Torque at 1,600 rpm	212Nm
Maximum PTO Power at Rated Engine Speed	48hp**
* Certified at BS AU 141a : (1971)	
** Manufacturer's Estimate	

Engine

Type	Diesel T 3.1524
Number of Cylinders	3
Injection	Direct
Bore	91.4 mm
Stroke	127.0 mm
Capacity (litres)	2.5 L
Compression Ratio	15.5 : 1
Aspiration	Turbo
Starting Aid	Thermostart
Throttle Control	Hand and Foot
Cooling	Water
Air Cleaner Type	Oil Bath
Air Pre-Cleaner	Over Bonnet, Air Swirl
Fuel Filter	Dual, High Capacity
Exhaust	Vertical Muffler Under Bonnet
Oil Cooler	Air Colled, Fin Type

Electrics

Voltage	12V, Negative Earth
Battery	110 Ah
Starter	2.2 kW
Alternator	32 Amp

Clutch

Type	Dual Clutch
Diameter	305,254 mm

Transmission

Type	Sliding Spur
Number of Gears	8 Forward, 2 Reverse
Road Speed at 2,250 Engine RPM	14.9/13-28 Rear Tyres
Gear	Speed (km/hr)
Forward 1 (First Low)	2.7
Forward 2	3.9
Forward 3	5.3
Forward 4	7.2
Forward 5 (First High)	10.7
Forward 6	15.6
Forward 7	21.3
Forward 8	28.7
Reverse 1 (Low)	3.6
Reverse 2 (High)	14.5

Power Take-Off

Type	Live
Engine Speed at 540 PTO rpm	1,789 rpm
Shaft Diameter	35mm
Number of Splines	6

Hydraulics

Functions	Draft Control Position Control Responce Control Constant Pumping
Pump Type	Reciprocating Ferguson Pump
Max. Oil Flow	16 L / min
Max. Pressure	21 MPa at Normal Operating Temperature
Max. Lift Capacity with Lower Links Horizontal	2,145 kg
Lower Links	With Cat, I & II Interchangeable Balls

Front Axle

Type	Box Section, Adjustable
------	-------------------------

Steering

Steering	Manual
----------	--------

Rear Axle & Brakes

Axle Type	Straddle with Epicyclic Reduction
Brake Type	Oil Immersed Multi-Disc
Brake Actuation	Mechanical
Parking Brake	Hand Lever Operated

Instrumentation

Gauges	Tachometer, Hour Meter, Fuel Level, Battery Condition & Water Temperature
Warning Lights	Direction Indicators, Electric Charge, Headlight Main Beam, Low Engine Oil Pressure, Brake Lights

Tyres

Front	7.50 - 16 (6PR)
Rear	14.9 / 13 - 28 (6PR)

Track Adjustment

Front	1,245 - 1,854 mm
Rear	1,423 - 2,134 mm

Weights & Dimensions

WEIGHT	
Max. Weight Front Axle	729 kg
Max. Weight Rear Axle	1,171 kg
Gross Weight	1,900 kg
DIMENSIONS	
Wheel Base	1,892 mm
Overall Length	3,260 mm
Overall Width (Min)	1,890 mm
HEIGHT	
Over Exhaust	2,220 mm
Over Steering Wheel	1,490 mm
TURNING CIRCLE	
With Brakes	5,840 mm
Without Brakes	6,580 mm
GROUND CLEARANCE	
Under Gear Box	400 mm

Capacities

Fuel Tank	47.5 L
Engine Pump	6.8 L
Cooling System	10.2 L
Hydraulic System	36.0 L
Steering Box	0.9 L
Oil Bath Air Cleaner	0.5 L

Standard Equipment

Weight Frame without Weights, Standard Tool Box with Set of Tools, Top Link End Cat I, Cat I & II Balls, Check Chains & Operator's Manual.

Optional Equipment

Front End Weights
Sun Canopy
Swinging Drawbar